

Received at: 4:27AM, 2/17/2005

2005年 2月17日 18時23分

BROTHER IP

NO. 3559 P. 3/5

12. The printing system according to claim 8, wherein the help list is displayed on said display unit of said personal computer to indicate the help list thereon.

13. The printing system according to claim 8, wherein basic help list data is stored in said storage device of the printer and a basic help list is printed out by said printing section of said printer when said printer and said personal computer are disconnected from each other.

14. The printing system according to claim 8, wherein basic help list data is stored in said storage device and a basic help list is generated by said display unit of said printer to indicate the basic help list when said printer and said personal computer are not connected to each other.

15. A peripheral device having at least one function, the peripheral device being capable of connecting with a host device having a data storage device storing help list data regarding how to set and how to use the at least one function of the peripheral device, the peripheral device comprising:

connectable

- an input/output interface *connected* to the host device;
- a help key through which a user inputs a command for requesting the help list;
- a read unit that reads out the help list data stored in the data storage device of the host device via the input/output interface when requested by operating the help key by the user; and
- when the peripheral device is connected to the host device and*
a display unit that shows a help list based on the help list data *read* ~~transmitted~~ from the host device via the input/output interface *when the peripheral device is connected to the host device*

16. The peripheral device according to claim 15, wherein the display unit includes a printer that prints out the help list on a recording medium *when the peripheral device is connected to the host device*

17. The peripheral device according to claim 15, wherein the display unit includes a display device that visually displays the help list thereon *when the peripheral device is connected to the host device*

Received at: 4:27AM, 2/17/2005

NO. 3559 P. 4/5

2005年 2月17日 18時24分

BROTHER IP

18. The peripheral device according to claim 15, further comprising a storage device that stores a basic help list data, wherein the display unit shows the basic help list when the peripheral device and the host device are disconnected from each other upon when requested by the user operating the help key.

19. A host device capable of connecting with a peripheral device having at least one function and a help key through which a user inputs a command for requesting the help list, the host device comprising:

an input/output interface ^{connectable} to the peripheral device;

a data storage device storing help list data regarding how to set and how to use the at least one function of the peripheral device;

a read unit that reads out the help list data stored in the data storage device when the host device is requested by operating the help key by the user, and connected to the peripheral device

a display unit that shows a help list based on the help list data read from the data storage device when the host device is connected to the peripheral device

20. The host device according to claim 19, wherein the display unit includes a printer that prints out the help list on a recording medium when the host device is connected to the peripheral device

21. The host device according to claim 19, where in the display unit includes a display device that visually displays the help thereon when the host device is connected to the peripheral device

22. A peripheral device having at least one function, the peripheral device being capable of communicating with a host device having a data storage device storing help list data regarding how to set and how to use the at least one function of the peripheral device, the peripheral device comprising:

an input/output interface ^{communicable} to the host device;

a help key through which a user inputs a command for requesting the help list;

received at: 4:27AM, 2/17/2005

NO. 3559 P. 5/5

2005年 2月17日 18時24分

BROTHER IP

a read unit that reads out the help list data stored in the data storage device of the host device via the input/output interface when requested by operating the help key by the user, and

when the peripheral device communicates to the host device
a display unit that shows a help list based on the help list data ^{read} transmitted from the host device via the input/output interface, when the peripheral device communicates to the host device